

GB Application

For pointing the joints of all types of ceramic tiles and slabs, terracotta tiles and slabs, natural stone, polygonal formats and pebble mats on ductile surfaces or substrates. Especially suitable for porcelain stoneware and for use on balconies and on terraces, on walls and floors, indoors and outdoors, and under-water.

Preparing the substrate

Allow tile adhesives to harden according to instructions on the package, embedding mortar for at least 3 weeks. Joints must be clean, uniformly moist, and deep. Remove any mortar or adhesives that may have entered the joints.

How-to-use

Water consumption: 25 kg : approx. 6.3 ltrs. of water. **Maturing time:** 3 minutes. Stir thoroughly once again.

Apply the mortar flush into the joints using a rubber squeegee. Wipe off any excess material. Let mortar stiffen. Then clean with a damp sponge.

Application time/temperature: approx. 20 minutes/5-25 °C. **To be walked on:** after 6-8 hours. All times given are based on temperatures of 15-20 °C and a relative humidity of 65 %. The technical data and shades of colour may be subject to change. **Storage life:** in closed, original containers, 12 months. Store dry. **Disposal:** recycle empty containers.

Please take note of details in the Harmful Substances Section and in the Technical Instructions Sheet.

Please Note

Differences in colour between the colours on the label and the hardened joint mortar may occur due to the printing techniques used. No warranty is given for any differences or deviations in colour in the joint itself which may be caused by the application of the mortar, or which could occur because of differences in the absorbent characteristics of the tiles or surface, for example. Make a test joint before using the mortar with porous, rough or fine-pore glazed surfaces.